查询VP0808供应商



# P-Channel Enhancement-Mode Vertical DMOS FETs

## Ordering Information

| $BV_{DSS}$ / $BV_{DGS}$ | $R_{DS(ON)}$ (max) | $I_{D(ON)}$ (min) | Order Number / Package |
|---|---|---|---|
| | | | TO-92 |
| -80V | 5.0Ω | -1.1A | VP0808L |

## Features

- ❏ Free from secondary breakdown
- ❏ Low power drive requirement
- ❏ Ease of paralleling
- ❏ Low $C_{ISS}$ and fast switching speeds
- ❏ Excellent thermal stability
- ❏ Integral Source-Drain diode
- ❏ High input impedance and high gain
- ❏ Complementary N- and P-channel devices

## Advanced DMOS Technology

These enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

## Applications

- ❏ Motor controls
- ❏ Converters
- ❏ Amplifiers
- ❏ Switches
- ❏ Power supply circuits
- ❏ Drivers (relays, hammers, solenoids, lamps, memories, displays, bipolar transistors, etc.)

## Package Option

TO-92

Note: See Package Outline section for dimensions.

## Absolute Maximum Ratings

| | |
|---|---|
| Drain-to-Source Voltage | $BV_{DSS}$ |
| Drain-to-Gate Voltage | $BV_{DGS}$ |
| Gate-to-Source Voltage | ± 30V |
| Operating and Storage Temperature | -55°C to +150°C |
| Soldering Temperature* | 300°C |

* Distance of 1.6 mm from case for 10 seconds.

11/12/01

Supertex Inc. does not recommend the use of its products in life support applications and will not knowingly sell its products for use in such applications unless it receives an adequate "products liability indemnification insurance agreement." Supertex does not assume responsibility for use of devices described and limits its liability to the replacement of devices determined to be defective due to workmanship. No responsibility is assumed for possible omissions or inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications, refer to the Supertex website: http://www.supertex.com. For complete liability information on all Supertex products, refer to the most current databook or to the Legal/Disclaimer page on the Supertex website.

## Thermal Characteristics

| Package | $I_D$ (continuous)* | $I_D$ (pulsed) | Power Dissipation | $\theta_{jc}$ °C/W | $\theta_{ja}$ °C/W |
|---|---|---|---|---|---|
| TO-92 | -0.28A | -3A | 1W | 125 | 170 |

* $I_D$ (continuous) is limited by max rated $T_j$.

## Electrical Characteristics (@ 25°C unless otherwise specified)

| Symbol | Parameter | Min | Typ | Max | Unit | Conditions |
|---|---|---|---|---|---|---|
| $BV_{DSS}$ | Drain-to-Source Breakdown Voltage | -80 | | | V | $V_{GS}$= 0V, $I_D$ =-10μA |
| $V_{GS(th)}$ | Gate Threshold Voltage | -1.0 | | -4.5 | V | $V_{GS}$ = $V_{DS}$, $I_D$ = -1mA |
| $I_{GSS}$ | Gate Body Leakage | | | -100 | nA | $V_{GS}$ = ±20V, $V_{DS}$ = 0V |
| $I_{DSS}$ | Zero Gate Voltage Drain Current | | | -10 | μA | $V_{GS}$ = 0V, $V_{DS}$ = Max Rating |
| | | | | -500 | | $V_{GS}$ = 0V, $V_{DS}$ = Max Rating $T_A$ = 125°C |
| $I_{D(ON)}$ | ON-State Drain Current | -1.1 | | | A | $V_{GS}$ = -10V, $V_{DS}$ = -15V |
| $R_{DS(ON)}$ | Static Drain-to-Source ON-State Resistance | | | 5.0 | Ω | $V_{GS}$ = -10V, $I_D$ = -1A |
| $G_{FS}$ | Forward Transconductance | 200 | | | m℧ | $V_{DS}$ = -10V, $I_D$ = -0.5A |
| $C_{ISS}$ | Input Capacitance | | | 150 | pF | $V_{GS}$ = 0V, $V_{DS}$ = -25V f = 1MHz |
| $C_{OSS}$ | Common Source Output Capacitance | | | 60 | | |
| $C_{RSS}$ | Reverse Transfer Capacitance | | | 25 | | |
| $t_{d(ON)}$ | Turn-ON Delay Time | | | 15 | ns | $V_{DD}$ = -25V, $I_D$ = -0.5A $R_{GEN}$ = 25Ω |
| $t_r$ | Rise Time | | | 40 | | |
| $t_{d(OFF)}$ | Turn-OFF Time | | | 30 | | |
| $t_f$ | Fall Time | | | 30 | | |
| $V_{SD}$ | Diode Forward Voltage Drop | | -1.2 | | V | $V_{GS}$ = 0V, $I_{SD}$ = -0.9A |

**Notes:**
1. All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300μs pulse, 2% duty cycle.)
2. All A.C. parameters sample tested.

## Switching Waveforms and Test Circuit









Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 744-0100 • FAX: (408) 222-4895
www.supertex.com

©2001 Supertex Inc. All rights reserved. Unauthorized use or reproduction prohibited.